


GRANDSTREAM NETWORKS

GS Search.exe

Version 1.0.0.17

Date: March 20, 2013

This utility will find and configure the IP address of Grandstream IP Video Surveillance products.

1. Run the Grandstream Search Tool.
2. Click  button begin device detection.
3. The detected devices will be displayed as output as shown like below:

[illegible]

4. New IP can be input to overwrite old IP by click “Modify IP”, the device will reboot to apply new IP.
5. PING button conveniently provided to make sure no IP duplication when using static IP.
6. Select “Use DHCP” and “Modify” to overwrite detected previously used static IP.

7. Wi-Fi Configuration can also be applied via the setting tab if initially found via wired LAN.

The screenshot displays the 'Wifi Configuration' tab of a network management interface. At the top, there are two tabs: 'IP Address Configuration' and 'Wifi Configuration'. Below the tabs is a table with the following columns: Index, SSID, Signal, Security Mode, and an empty column. The table contains several rows of data, but they are mostly empty. Below the table are three buttons: 'Scan', 'Select', and 'Delete'. Further down, there is a checkbox labeled 'Enable Wifi' which is checked. Below this are three input fields: 'SSID', 'Key', and 'Security Mode'. The 'Security Mode' field is a dropdown menu. At the bottom of the configuration section is a 'Save' button.

Index	SSID	Signal	Security Mode	

☒ Enable Wifi

SSID

Key

Security Mode

8. If GSurf_Pro installed, the embedded "Search Tool" of GSurf_Pro SHOULD be used instead of this one.