



HT286 AND HT701 COMPARISON TABLE

Specifications	HT286	HT701
Telephone Interfaces	1 FXS port	1 FXS port
Network ports	1 (10 Mbps)	1 (10/100 Mbps)
Universal Power Supply	5V ; 1.2 A	12V ; 0.5A
Short and Long Haul	3REN, up to 1 Km on 24 AWG Lines	5REN , up to 1 Km on 24 AWG Lines
Voice Codec	PCMU, PCMA, G723.1, G729, G726-32, iLBC	PCMU, PCMA, G723.1, G729, G726-32, iLBC
Provisioning	TFTP/HTTP	TFTP/HTTP/ HTTPS, Encrypted XML and TR-069
Telephony Features	Hold, transfer, forward, 3-way conference, call waiting, DTMF via SIP INFO/RFC2833/IN-Audio, Dial Plan (HT701 only)	
Security	NO	SRTP, TLS/TCP, Secure Provisioning
Manageability	IVR, Web UI, Provisioning File	IVR, Web UI, Provisioning File, TR-069
Fax Mode	T.38	T.38
Caller ID	Bellcore Type 1 & 2, ETSI, BT, NTT, DTMF Based CID	Bellcore Type 1 & 2, ETSI, BT, NTT, DTMF Based CID
ADVANCED SPECIFICATIONS		
LEDs	1 Led (Power and status indication)	4 Leds (Power, Internet, Link/ACT, Phone) with advanced Indication
SIP Transport	UDP	UDP, TCP, TLS
Reset options	Full reset by IVR only	Full/ISP/VOIP reset by web, Full reset by IVR and reset button
Language	English	English, Chinese and Spanish (IVR)
Sip Sever Failover	DNS SRV	DNS SRV and Failover Sip Server
Security Control	n/a	TLS and SIPS
Mounting	Laying flat	Laying flat or wall mounting
Disconnect methods	Busy Tone, Polarity Reversal	Busy Tone, Polarity Reversal, Loop current