



HT702

NEW PRODUCT SAME RELIABILITY

Specifications	HT502	HT702
Telephone Interfaces	2 FXS ports (RJ11)	2 FXS ports (RJ11)
Network Ports	2 (10M/100Mbps Full Duplex ports (RJ-45))	1 (10M/100Mbps Full Duplex ports auto-sensing Ethernet port (RJ45))
Universal Power Supply	12V, 500mA	
Short and Long Haul	3 RENS: Up to 1km on 24 AWG line	
Telephony Features	Caller ID Display or Block, Call Waiting with Caller ID, Call Waiting/Flash, Blind or Attended Call Transfer, Hold, Call Forward, Do Not Disturb, 3-Way Conferencing, message waiting, call-return service, DTMF via In Audio, RFC2833, and SIP INFO	
Voice Codec	G.711 Annex I (PLC) and Annex II (VAD/CNG format), G.723.1, G.729A/B/E, G.726-40/32/24/16, iLBC, dynamic jitter, buffer, advanced line echo cancellation	G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.729A/B, G.726 (40/32/24/16), iLBC, dynamic jitter, buffer, advanced line echo cancellation
Provisioning & Management	IVR, UPnP, TFTP, HTTP, HTTPS, Telnet, TR-069, secure and automated provisioning using AES encrypted or non-encrypted Binary or XML file, syslog	
Security	SRTP, TLS/SIPS/HTTPS, Syslog support, Telnet, remote management using Web Browser	
Fax Mode	T.38, Pass-Through	
LED Pattern	Basic Number of Indications	Advanced Number of Indications
Caller ID	Bellcore Type 1 & 2, ETSI, BT, NTT, and DTMF- based CID	
ADVANCED SPECIFICATIONS		
LEDs	Power, WAN,LAN, PHONE 1 and PHONE 2	Power, Internet, LINK/ACT, PHONE 1 PHONE 2
SIP Transport	UDP, TCP, TLS	
Reset options	Full via IVR, Full via Factory Reset Button, Full/ISP/VoIP via Web (HT702 only)	
Language	English, Chinese and Spanish (IVR)	
Sip Sever Failover	DNS SRV and Failover Sip Server	
Security Control	TLS and SIPS	
Mounting	Laying flat or Standing up using the included stand	
Disconnect methods	BusyTone, Polarity Reversal, Loop Current	
Built-in Router	Yes	No
List Price	\$69	\$49