



## Specifications

CO Lines	8
Analog Extensions	24
RJ21 Connectors	1 for FXS and 1 for FXO
SIP Extensions	8
SIP Trunks	4
Network Interfaces	1 10/100Base-T Ethernet
Protocol	SIP (RFC3261)
Transport	UDP, TCP, TLS, SRTP
DTMF	RFC4733, SIP INFO, In-band
Codec	G.711 (a-law, u-law), G.722, G.726, G.729 A/B, GSM, iLBC , Speex
Console Port	1
SD Card Slot	1
Dimensions	440 mm × 250 mm × 44 mm

## Features

Attended Transfer	Automated Attendant (IVR)
Automatic Upgrade	Backup and Restore
Blind Transfer	Busy Camp-on
Call Barge-in	Call Detail Records
Call Duration Restriction	Call Forwarding (All, Busy, No Answer)
Call Hold	Caller ID
Call Parking	Call Pickup
Call Recording	Call Report
Call Report Export	Call Waiting
Conferencing	Custom Prompts
Do Not Disturb (DND)	Fax to Email
Follow Me	Hotline
Intercom	Last Caller Routing
Linkus Mobile Client	Music on Hold
Music on Transfer	One Touch Record
Queues	Ring Group
Seize a Line	Speed Dial
T.30 & T.38 Fax	Time Condition Routing
Timed Reminder	System Logs

